## Listing and Amendments to the Claims

This listing of claims will replace the claims that were published in the PCT Application and the International Preliminary Examination Report:

- 1. (currently amended) A router or bridge device (4) characterized in that it comprises comprising
- -means (13)—for connection to a first network (6)—and means for connection to a second network (12);
- -an application for selecting configuration parameters, wherein the application applies a template for presenting parameters to a user, said template being uploadable to said device.
- 2. (original) Device according to claim 1, comprising a plurality of templates.
- 3. (original) Device according to claim 2, wherein the application comprises means for generating a template selection display to a user.
- 4. (currently amended) Device according to claim 2 or 3, wherein the application comprises means for loading a template from at least one of: a host device connected to the second network, a server connected to the first network.
- 5. (currently amended) Device according to one of the claims 1 to 4 claim 1, wherein said application is a web server provided with means for generating pages for display on a remote display.
- 6. (original) Device according to claim 5, wherein said display is part of a host device comprising a browser for accessing the pages and for interacting with a user for selection of the configuration parameters.

EXPRESS MAIL LABEL NO. EV 365397377US

PF020154

CUSTOMER NO.: 24498

7. (currently amended) Device according to claim one of the claims 1 to 6 1, wherein the application is adapted to generate at least one configuration file based on at least one template.

8. (original) Device according to claim 7, comprising a factory default configuration.

9. (currently amended) Device according to claim 7 and 8, comprising a configuration predetermined by an Internet service provider.

10. (original) Device according to claim 9, wherein a priority is established between a user configuration, an internet service provider configuration and a factory default configuration in that order and wherein a parameter required by device software not found in one configuration is taken from a lower priority configuration.